

## ▶ AP20

### ENHANCED POLYMER SEALANT

AP20 is an enhanced polymer sealant. It is a highly viscous, highly flexible, zero VOC, solvent and isocyanate free, environmentally friendly, moisture cured, waterproof trowel/butter grade enhanced polymer formula. It can be used in a variety of applications, such as sealing around doors, windows and siding, connection joints of wood and metal structures, kitchen and bath sealing applications, and concrete joints. It is designed to create a watertight liquid flashing for intricate areas and details. AP20 is high performing, durable, reflective, UV resistant, non-yellowing, and has excellent vertical hang.

#### FEATURES & BENEFITS

- Easy Application
- Weatherproof
- Paintable
- No VOC's
- Solvent & Isocyanate Free
- Resists Mildew
- Environmentally Friendly
- Resistant to UV
- Resistant to Chemicals
- Excellent Vertical Hang

#### TYPICAL USES

- Manufacturing
- Sealing Doors, Windows & Siding
- Connection Joints of Wood and Metal Structures
- Kitchen & Bath Sealing
- Installation & Insulation of Facade Elements
- Building Facades
- Roofing Constructions
- Concrete Joints

#### DIRECTION OF USE

##### ***Surface Preparation***

Review all technical data sheets, system sheets, labels, instructions, SDS, and Guide Specifications before applying. Perform a test area for material familiarity and performance. Surface must be dry and clean. Do not apply over contaminated surfaces. Remove dirt, and foreign material detrimental to adhesion or application of AP20.

# ▶ AP20

ENHANCED POLYMER SEALANT

▶ The Brand  
You can Trust!

## DIRECTION OF USE

### **Application**

For 10 oz tubes and 20 oz sausages, refer to the Application Chart for bead sizes and application rates. Cut nozzle to the appropriate bead size. Apply with caulking gun. Push sealant into the substrate and seal any openings. Spread evenly, and leave smooth. Cure times will depend on environmental conditions. As humidity rises, the cure time will decrease. At 72°F (22°C), 50% R.H., a 1/4" bead will cure in 24 hours. Allow sealant to dry 2-4 hours (longer in cool or humid conditions) before painting with latex or oil-based paints.

### **Limitations**

Do not apply over moist/damp surfaces. Always review Safety Data Sheet (SDS) for health hazards and information on Personal Protective Equipment (PPE). Apply in temperatures above 40°F (4°C). Do not apply when rain or freezing temperature are forecasted within 24 hours. Cooler temperatures and higher humidity will slow down dry time.

## SAFETY & PRECAUTIONS

### **Cleanup**

Clean up excess wet caulk with a damp sponge before it skins over. Excess dried caulk must be cut or scraped away. Clean hands and tools with warm water and soap, or other equal solutions as required by job conditions and as permitted by local, state, and federal regulations.

### **Storage & Handling**

Keep containers closed and stored in a dry, cool place away from heat, sparks, open flame, and moisture. Keep material stored above 65°F (18°C) and on wood pallets off concrete floors. Open containers, such as pails and drums, should be blanketed with dry nitrogen before resealing.

### **Shelf Life**

10oz tubes and sausages – 12 months.  
Practice proper stock rotation.

### **Safety**

FIRST-AID: Read technical data sheet and safety data sheet before use. Avoid breathing dust/fume/gas/mist/vapors/spray. In case of inadequate ventilation, wear respiratory protection. Specific treatment (see Section 4 of SDS). Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. IF EXPOSED OR CONCERNED: Seek medical advice/attention. IF IN EYES: Rinse cautiously with water. If eye irritation persists, seek medical advice/attention. IF INHALED: Remove person to fresh air. If experiencing respiratory symptoms, call a Poison Center/Doctor. IN CASE OF FIRE: Check Section 5 (Fire Fighting Measures).

# ▶ AP20

ENHANCED POLYMER SEALANT

▶ The Brand  
You can Trust!

## TECHNICAL DATA

<b>Tack Free Time</b>	> 15 minutes @ 77°F (25°C) / 50% RH
<b>Elongation</b>	≥ 100% (ASTM D-412C)
<b>Tensile Strength</b>	≥ 0,5 Mpa (ASTM D-412C)
<b>Hardness, ASTM-2240</b>	35 ± 5 (ASTM D-53505) Shore A
<b>Specific Gravity</b>	1,71 ± 0,03 g / cm <sup>3</sup>
<b>Application Temperature</b>	41°F (5°C) to 95°F (35°C)
<b>Temperature Resistance</b>	-40°F (-40°C) to 194°F (90°C)
<b>Volatile Organic Compound (VOC)</b>	0 grams / liter

\* This information is intended only as a guide for design purposes. The values shown are the average values obtained from laboratory samples. The test methods were performed per the ASTM Book of Standards. Higher or lower temperature & humidity conditions will affect dry time. The information contained herein is for purposes of identifying the product and does not constitute a warranty that the product will conform to that description. Product specifications and performance will vary depending on application methodologies, raw materials and other factors.

Please read all information in the general guidelines, technical data sheets, application guide, and safety data sheets (SDS) before applying material. Published technical data and instructions are subject to change without notice. Contact your local Ghemco Representative or visit our website for current technical data and instructions. DISCLAIMER: All guidelines, recommendations, statements, and technical data contained herein are based on information and tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the user's responsibility to satisfy himself, by his own information and tests, to determine suitability of the product for his own intended use, application and job situation and user assumes all risk and liability resulting from his use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones that may exist. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements, whether verbal or in writing, other than those contained herein shall not be binding upon the manufacturer, unless in writing and signed by a corporate officer of the manufacturer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and Ghemco makes no claim that these tests or any other tests, accurately represent all environments.